



FD08 Charging Adapter (screen display)

Allows power extraction from charging station or Plug via Type 2 interface.

SUPERGENIE.



T1-T2 1P



Electricity Consumption
LED display



Emergency Power Supply



T2-T1 1P

T2-GBT 1P

T1-GBT 1P

GBT-T2 1P

GBT-T1 1P

T2-GBT 3P

GBT-T2 3P

Product Type	T2-T1 1P	T2-GBT 1P	T1-T2 1P	T1-GBT 1P	GBT-T2 1P	GBT-T1 1P	T2-GBT 3P	GBT-T2 3P
Applicable	Type 2 to Tpye 1	Type 2 to GBT	Type 1 to Tpye 2	Type 1 to GBT	GBT to Tpye 2	GBT to Tpye 1	Type 2 to GBT	GBT to Tpye 2
Rated power	7kW MAX						22kW MAX	
Rated Voltage	AC 110V~250V(single-phase)						AC 250V/AC480V (three-phase)	
Rated Current	32A MAX							
Display Method	LED (with kwh)						None	
Startup mode	Plug and Play							
Dimensions	φ70mm*174mm(H)							
Unplug lifetime	>10000 times							
Working Environment	-20℃~-50℃, <2000m, 5%RH~95%RH							
Certificatio	CE/FCC							
Feature	OEM/ODM compatible, with screen charging display, suitable for various charging standard chargers and adapters for charging ports.							