

Specifications

| Model No. | Voltage | LED Type | Color | LEDs / M | CRI | Power | Luminous | Efficacy | IP Grade | Warranty | Operational Length (m) |
|---------------------|---------|----------|------------|----------|-----|----------|----------|----------|----------|----------|------------------------|
| AN-DBM1405Ex - D24 | 24V DC | 2835SMD | 2700-6500K | 112 pcs | >80 | 13.6 W/m | 1200lm/M | 90 lm/W | IP68 | 5 years | 10m |
| AN-DBM1405Ex - D24 | 24V DC | 2835SMD | 2700-6500K | 154 pcs | >80 | 16 W/m | 1440lm/M | 90 lm/W | IP68 | 5 years | 10m |
| AN-DBM1405Ex - D48 | 48V DC | 2835SMD | 2700-6500K | 112 pcs | >80 | 13.6 W/m | 1200lm/M | 90 lm/W | IP68 | 5 years | 30m |
| AN-DBM1405Ex - D48 | 48V DC | 2835SMD | 2700-6500K | 154 pcs | >80 | 16 W/m | 1440lm/M | 90 lm/W | IP68 | 5 years | 30m |
| AN-DBM1405Ex - A110 | 110V AC | 2835SMD | 2700-6500K | 112 pcs | >80 | 15.6 W/m | 1500lm/M | 90 lm/W | IP68 | 5 years | 50m |
| AN-DBM1405Ex - A110 | 110V AC | 2835SMD | 2700-6500K | 140 pcs | >80 | 18.6 W/m | 1700lm/M | 90 lm/W | IP68 | 5 years | 50m |
| AN-DBM1405Ex - A230 | 230V AC | 2835SMD | 2700-6500K | 132 pcs | >80 | 15.6 W/m | 1500lm/M | 90 lm/W | IP68 | 5 years | 100m |
| AN-DBM1405Ex - A230 | 230V AC | 2835SMD | 2700-6500K | 144 pcs | >80 | 18.6 W/m | 1700lm/M | 90 lm/W | IP68 | 5 years | 100m |

NOTE: 1. Above parameters are based on 1M standard products;
 2. $\pm 10\%$ is allowed for power and luminous flux;
 3. Operational Length refers to the max. length with single power feed up to (m);
 4. Above parameters are typical values.