

| | |
|----------------------------|---|
| Types | Description |
| Product category | Aluminum alloy rolling door |
| Material | Aluminum alloy |
| Size | Custom made |
| Price | Calculated according to the installation method |
| Door style | Multiple choices |
| Performance | No fading, no layer, no yellowing, durable |
| Colour | Beige, matt white, Green,Blue, Black, Coffee, electrophoretic champagne, electrophoretic silver white, mahogany wood grain, golden oak wood grain etc.. |
| Surface | The surface adopts advanced technology such as powder electrostatic spraying, thermal transfer wood grain, electrophoresis,anodized oxidation, etc. |
| Rolling door profile | Appropriate hardness, flexibility and elasticity |
| Muffler and sealing code | Made of high-quality virgin rubber, quieter, more lubricated, and more beautiful |
| Rolling door configuration | 1. Door panel |
| | 2. Five-inch tube (reel)/sealing + end plate, note: when using an external motor, a five-inch tube is required . When a tubular motor is used, it can be equipped with a sealing box. |
| | 3. Motors are divided into external motors and tubular motors |
| | 4. Guide groove |
| Note | 1.Door stack ≥ 10 cm, door lintel ≥ 35 cm, Can be installed inside, accessories + monorail |
| | 2.Door stack ≥ 10 cm, 35 cm $>$ Door lintel ≥ 20 cm, Can be installed inside, accessories + double track Straight wall |
| | 3.(no door buttress and no lintel), can be installed in the middle |